

BATTERY STRAPPING TOOL FOR
POLYESTER STRAP WITH VIBRATION SEALING



NEW

ONE PUSH OPERATED

TECHNICAL SPECIFICATIONS	
DIMENSIONS	
Length	300 mm • 11.8"
Width	150 mm • 5.9"
Height	160 mm • 6.3"
Weight	3.9 Kgs • 8.6 lbs
FEEDING	
Battery	14.8V-2 A/h LI-PO
PERFORMANCE	
Max. tension force	2500N
Tensioning speed	16mt/m
Sealing	Vibration sealing
Joint strength	80% of breaking strength*

* variable according to strap type

OPERATING MODES
Fully Automatic
Semi Automatic
Manual

With Fully Automatic Mode tensioning, welding and strap cutting are performed with only one push of a button.

MODEL			
CODE	TYPE	STRAP	THICKNESS
T249997	ITA24 / 13-16mm with one battery	PP-PET	0.5 mm - 0.019" • 1.05 mm - 0.041"
		13-16 mm • 1/2"-5/8"	
T2499971	ITA24 / 13-16mm with one battery and charger	PP-PET	0.5 mm - 0.019" • 1.05 mm - 0.041"
		13-16 mm • 1/2"-5/8"	
T2499972	ITA24 / 13-16mm with two batteries and charger	PP-PET	0.5 mm - 0.019" • 1.05 mm - 0.041"
		13-16 mm • 1/2"-5/8"	

POLYESTER STRAP



POLYESTER STRAP



POLYPROPYLENE STRAP

